

DCDALF4AN series

double check detector assembly
lead free



job name:	
job location:	
engineer:	
contractor:	
tag:	
po#:	
rep:	
wholesale dist.:	

description

the 2-1/2" - 12" lead free double check detector assembly shall be an Apollo model DCDALF4AN or DCDA2LF4AN. the assembly shall be manufactured in America and carry a 5-year Apollo factory warranty. the TriForce™ center-stem guided check valves shall feature reversible silicone rubber seat discs. the check valves shall be held in place by drop-in retainers (2-1/2" - 6") or SS studs & nuts (8" - 12"). access to the check valves shall be by an Apollo quick-connect SS coupling (2-1/2" - 6") or grooved couplings (8" - 12"). the bodies shall be domestic SS in 2-1/2" - 8" sizes and FDA epoxy-coated ductile iron in 10" & 12" sizes. the assembly is a mainline double check valve with a type 2 bypass consisting of a lead free* single check (SCV) and meter bypassing the mainline second check to prevent backflow while accurately measuring all flows up to 2 gpm with the mainline 2nd check remaining closed. assemblies with the optional Type 1 bypass consist of a lead free* double check valve and meter which bypasses both mainline checks and accurately meters all flows up to 2 gpm with both mainline checks closed. the Apollo ball valve test cocks shall have SS handles. the assembly shall prevent contamination of the potable water supply due to back-siphonage or backpressure from substances that are non-health hazards. the pressure drop across the assembly shall be documented by an independent laboratory.

features

- domestic stainless steel body: 2-1/2"-8"
- fda epoxy coated ductile iron body: 10" & 12"
- easy maintenance: no special tools required
- drop-in check retainers: 2-1/2"-6"
- bolted-in checks: 8"-12"
- low pressure loss as documented by an independent approval laboratory
- center stem guided triforce™ check valves
- 5 year warranty
- small installation space required - small footprint
- chloramine-resistant elastomers
- lead free standard
- optional valve setters eliminate need for thrust blocks below grade
- us patent nos.: 6,443,184; 7,025,085; 7,533,699
- made in the usa (d option)
- optional mounting of bypass on either side for ease of installation

approvals

- ASSE 1048 (with meter)
- UL, ULC classified
- CSA B64.5
- approved by the foundation for cross-connection control and hydraulic research at the university of southern california (2-1/2" - 8" type 1 bypass, 10" - 12" type 2 only)
- FM approved
- NSF/ANSI 61 water quality
- NSF/ANSI 372 lead Ffree

performance rating

- maximum working pressure: 175 psi
- temperature range: 33°F - 140°F, 180°F intermittent

standard materials list

body (2-1/2" - 8")	304 stainless steel
body (10" & 12")	FDA epoxy coated ductile iron
covers (2-1/2" - 6")	glass filled PPO/SS
covers (8")	304 stainless steel
covers (10" & 12")	FDA epoxy coated ductile iron
check valves	bronze/glass-filled PPO/SS
springs	stainless steel
seat discs	chloramine-resistant silicone

part number matrix

4ANLF	6 X	X	X	X [X]	X
	BYPASS SUB-ASSEMBLY OPTIONS	SIZE	METER OPTION	SHUT-OFF VALVES (INLET X OUTLET)	OPTIONS
4ANLF - LEAD FREE	0 - TYPE 1 W/ 1/2" DOUBLE CHECK	9 - 2-1/2"	C - CUBIC FEET/MIN	3 - OS&Y FLANGE X OS&Y FLANGE	D - DOMESTIC ASSEMBLY
	2 - TYPE 2 W/1/2" SINGLE CHECK (STD)	0 - 3"	E - GALLONS/MIN	4 - OS&Y FLANGE X MONITORED (MON.) BUTTERFLY VALVE GROOVE'	
	3 - TYPE 1 W/ BYPASS ON LEFT*	A - 4"	G - LESS METER	6 - OS&Y FLANGE X POST INDICATOR FLANGE	
	4 - TYPE 2 W/ BYPASS ON LEFT*	C - 6"		7 - OS&Y FLANGE X OS&Y GROOVE	
		E - 8"		8 - OS&Y GROOVE X OS&Y GROOVE	
		G - 10"		9 - MON. BUTTERFLY VALVE GROOVE X MON. BUTTERFLY VALVE GROOVE'	
		H - 12"		10 - OS&Y FLANGE X POST INDICATOR GROOVE	
				13 - POST INDICATOR FLANGE X MON. BUTTERFLY VALVE GROOVE'	
				14 - POST INDICATOR FLANGE X POST INDICATOR FLANGE	
				16 - MON BUTTERFLY VALVE GROOVE X POST INDICATOR FLANGE'	
				17 - POST INDICATOR FLANGE X OS&Y GROOVE	
				18 - OS&Y GROOVE X POST INDICATOR GROOVE	
				19 - MON. BUTTERFLY VALVE GROOVE X POST INDICATOR GROOVE	
				20 - POST INDICATOR FLANGE X OS&Y FLANGE	
				21 - POST INDICATOR GROOVE X OS&Y GROOVE	
				22 - POST INDICATOR GROOVE X MON. BUTTERFLY VALVE GROOVE'	
				23 - MON. BUTTERFLY VALVE GROOVE X OS&Y FLANGE	

EXAMPLE: 4ANLF 62A E7 = 4" size Lead Free Double Check Detector Assembly with OS&Y flanged inlet x OS&Y grooved outlet shut-off valves with Type 2 bypass w/ meter in GPM


*orientation of bypass looking downstream. standard is right hand side. left hand is on opposite side
 †butterfly valves not available in 12" size.

*lead free: the wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. complies with federal public law 111-380. ANSI 3rd party approved and listed.



DCDALF4AN series

double check detector assembly
lead free



dimensions

nominal dimensions are shown. allowances must be made for manufacturers' tolerances (3 1/8" (3 mm) per joint)


DIMENSIONS	2-1/2"	60MM	3"	75MM	4"	100MM	6"	150MM	8"	200MM	10"	250MM	12"	300MM
A (Centerline to Centerline)	12.5	318	12.5	318	14	356	16	406	18.5	470	21	533	26.8	681
B (Lay Length Space - Butterfly Valves)	27.8	705	30.0	762	31.0	787	34.3	870	38.0	965	45.8	1162	N/A	N/A
B (Lay Length Space - Gate Valves)	31	787	31	787	31.8	808	36.3	922	41.5	1054	49	1245	55.8	1417
C (Butterfly Valves - Top to Flange)	18.8	476	19.0	483	20.8	527	25.0	635	29.5	749	34.8	883	N/A	N/A
C (Gate Valves - Flange to Top)	19.6	498	20	508	22.5	572	27.8	706	32.1	815	40	1016	44	1118
D (Centerline To Bottom - Butterfly Valves)	11.5	292	11.8	298	12.5	318	14.6	371	17.9	454	19.8	502	N/A	N/A
D (Centerline to Bottom - Gate Valves)	13	330	13.5	343	14.9	378	18	457	21.4	544	24.8	630	28.8	732
E (Maximum Width - Butterfly Valves)	13.1	333	13.1	333	15.3	389	16.1	410	23.5	597	24.3	618	15.3	389
F (Centerline Width - Butterfly Valves)	8.6	219	9.6	244	10.9	276	12.5	318	16.5	419	18.1	460	N/A	N/A
F (Maximum Width - NRS/PI Gate Valves)	15.6	396	16.9	429	18.6	472	23.8	605	29.1	739	36.3	922	40	1016
F (Maximum Width - OS&Y Valves Open)	22.7	575	24.2	514	26.6	679	34.4	875	44.9	1140	57.9	1471	61.9	1572
G (Centerline to Width - Butterfly Valves)	8	203	8.4	213	9	229	10.9	277	12.9	328	13.5	343	N/A	N/A
G (Centerline to Width - NRS/PI Gate Valves)	11.8	300	13	330	14	356	17.8	452	21	533	24.5	622	30	762
G (Centerline to Width - OS&Y Valves Open)	18.8	478	20.3	515	22.1	562	29.4	747	36.8	934	45.2	1147	52.2	1326
H (Check Removal Clearance)	6	152	6	152	6	152	8	203	8.5	216	12	305	12	305
Test Cocks (NPT)	1/2"	13	1/2"	13	1/2"	13	3/4"	20	3/4"	20	3/4"	20	3/4"	20
WEIGHTS	LB.	KG	LB.	KG	LB.	KG	LB.	KG	LB.	KG	LB.	KG	LB.	KG
Net Wt. (w/Butterfly Valves)	108.4	49	113.4	51	138.4	63	196.4	89	489.0	222	1013.0	459	N/A	N/A
Ship Wt. (W/Butterfly Valves)	169.4	77	174.4	79	199.4	90	276.4	125	624.0	283	1203.0	546	N/A	N/A
Net Wt. (w/ Post Indicator Valves)	84	38	101	46	134	61	257	117	622	283	1292	587	1770	805
Ship Wt. (w/ Post Indicator Valves)	145	66	161	73	195	89	337	153	757	344	1482	674	1960	891
Net Wt. (w/ OS&Y Valves)	102	46	117	53	165	75	316	144	697	317	1407	640	1885	857
Ship Wt. (w/ OS&Y Valves)	163	74	178	81	226	103	396	180	832	378	1597	726	2075	943

internal body connections are grooved on 2-1/2" to 10" sizes.
internal body connections are flanged on 12" size.

DCDALF4AN series

double check detector assembly
lead free

FLOW CURVES



flow curves directly reflect data collected by an independent laboratory.
 flow curves shown were recorded with gate shut-off valves. contact factory for more information.
 all data points are based on ASSE increasing flow data, from zero GPM to rated flow (opening curve).
 for high flow rates/pressure loss information - contact factory.