



Certificate number: 2010710

Date issued 6th October 2020

Date expired 5th October 2025 Original/Amendment Original

Kiwa UK Regulation 4 (KUKreg4) Approval

ATS3 – Without Production Surveillance

Issued by Kiwa Watertec (UK)

Evaluation Guideline: Kiwa UK – EG004
Reference Standards: Regulators Specification
Model Designations: see Appendix

Factor: Pegler Yorkshire Group Ltd

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied on to comply with the above Evaluation Guideline and Standards, and can be marked with the KUKreg4mark.

The intended use of this certificate is for compliance with Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales; 2009 Northern Ireland and 2014 Byelaws Scotland

This certificate has been issued in accordance with the Kiwa regulations for product certification

Signed on behalf of Kiwa Watertec

David Jay,
Business Unit Manager – Authorised Signatory
Kiwa Watertec

CERTIFICATE

3901770301

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate issued to:
Pegler Yorkshire Group Ltd
St. Catherines Avenue
Doncaster
South Yorkshire
DN4 8DF



UK Approval Certificate (page 2 of 2)

Appendix to Certificate 2010710

The following products are covered by this certificate -

PRODUCT DESCRIPTION Range of gate valves (gunmetal) with gunmetal bronze wedges, brass spindle and PTFE seals. Maximum working pressure 20.0 bar. Maximum operating temperature 100°C
MODEL(S) 1070/125 Product Codes = 103007, 103008, 103009, 103010, 103011, 103012, 103013, 103014, 103015. 1070/125PT Product Codes = 103047, 103048, 103049, 103050, 103051, 103052, 103053, 103054, 103055. 1070/125 Lockshield Product Codes = 103057, 103058, 103059, 103060, 103061, 103062
SIZE: 1070/125 Taper Thread (½" female BSP inlet/outlet - 4" female BSP inlet/outlet) 1070/125PT Parallel Tread (½" female BSP inlet/outlet - 4" female BSP inlet/outlet) 1070/125 lockshield (½" female BSP inlet/outlet - 2" female BSP inlet/outlet).
SCOPE: <ul style="list-style-type: none"> - Supplier recommended Maximum Working Pressure 20 Bar & Maximum Temperature 100°C - Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C - Above Ground use only
MATERIALS Non-Metallic Materials assessed (BS6920) to point of discharge
BACKFLOW PROTECTION NOTES N/a
MARKING Pegler England Cast on Body
ADDITIONAL NOTES N/a

Extra Notes