



Certificate number: 2310786 (iss)

Issued 25/10/2023

Expires 25/10/2028

## Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

### Aalberts intergrated piping systems Ltd.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

**Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.**

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory  
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

# CERTIFICATE

Kiwa Watertec  
(A Trading Division of Kiwa Ltd)  
26A Rassau Industrial Estate  
Ebbw Vale  
Gwent  
NP23 5SD  
United Kingdom  
T +44 (0)1495 308185  
[uk.water@kiwa.com](mailto:uk.water@kiwa.com)  
[www.kiwa.co.uk](http://www.kiwa.co.uk)

**Certificate Issued to:**  
Aalberts intergrated piping systems Ltd  
St Catherines Avenue  
Doncaster  
DN4 8DF  
united kingdom



KUKreg4

# Product Certificate

Appendix to Certificate number: 2310786

The following products belong to this certificate

<b>PRODUCT DESCRIPTION</b> Range of spherical valves with DZR brass bodies, incorporating chromium plated brass ball and PTFE seats. The valve bodies incorporate 'Tectite' push-fit end connections. For use with copper (manufactured to BS 2871), PEX and polybutylene (manufactured to BS 7291) pipe. ATS3 – Without Production Surveillance.																	
<b>MODEL(S)</b> <table border="0"> <tr> <td>15mm</td> <td>TX300 Ball Valve</td> <td>66001</td> </tr> <tr> <td>22mm</td> <td>TX300 Ball Valve</td> <td>66004</td> </tr> <tr> <td>15mm x 3/4"</td> <td>T809 Straight Application Valve</td> <td>66010</td> </tr> <tr> <td>15mm x 3/4"</td> <td>T809B Bent Application Valve</td> <td>66011</td> </tr> <tr> <td>15mm x 3/4"</td> <td>T809T Tee Application Valve</td> <td>66012</td> </tr> </table>			15mm	TX300 Ball Valve	66001	22mm	TX300 Ball Valve	66004	15mm x 3/4"	T809 Straight Application Valve	66010	15mm x 3/4"	T809B Bent Application Valve	66011	15mm x 3/4"	T809T Tee Application Valve	66012
15mm	TX300 Ball Valve	66001															
22mm	TX300 Ball Valve	66004															
15mm x 3/4"	T809 Straight Application Valve	66010															
15mm x 3/4"	T809B Bent Application Valve	66011															
15mm x 3/4"	T809T Tee Application Valve	66012															
<b>SIZE:</b> See model.																	
<b>SCOPE:</b> Manufacturer recommended maximum working pressure 16 Bar@65°C & 10 bar@92°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C Above ground use only.																	
<b>MARKING</b> Tectite' on handle. 'Tectite', model, date, PN16 and CR mark on valve body.																	
<b>MATERIALS</b> Non-metallic materials assessed (BS6920) to point of discharge.																	
<b>BACKFLOW PROTECTION NOTES</b> N/A.																	
<b>ADDITIONAL NOTES</b> All water contact & exposed components satisfy opacity requirements.																	

**Extra Notes**