



Certificate number: 2010723

Date issued 21st October 2020

Date expired 20th October 2025 Original/Amendment Original

Kiwa UK Regulation 4 (KUKreg4) Approval

ATS3 – Without Production Surveillance

Issued by Kiwa Watertec (UK)

Evaluation Guideline: Kiwa UK – EG004
Reference Standards: Regulators Specification
Model Designations: see Appendix

Factor: Pegler Yorkshire Group Ltd

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied on to comply with the above Evaluation Guideline and Standards, and can be marked with the KUKreg4mark.

The intended use of this certificate is for compliance with Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales; 2009 Northern Ireland and 2014 Byelaws Scotland

This certificate has been issued in accordance with the Kiwa regulations for product certification, which is managed in accordance with ISO/IEC 17065.

Signed on behalf of Kiwa Watertec

David Jay,
Business Unit Manager – Authorised Signatory
Kiwa Watertec

CERTIFICATE

3901770301

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate issued to:
Pegler Yorkshire Group Ltd
St. Catherines Avenue
Doncaster
South Yorkshire
DN4 8DF



The following products are covered by this certificate -

| PRODUCT DESCRIPTION | | |
|---|-------------------------------|------------------------------------|
| Range of copper fittings for use with EN 1057 copper tube. For above ground use only. Maximum working pressure 18.6 bar. Maximum operating temperature 100°C. | | |
| ATS3 – Without Production Surveillance | | |
| MODEL(S) | | |
| N1: Straight Coupling | | N61 Stop End |
| Product code & size | | 89090 – 67mm |
| 88030 – 67mm | | 89694 – 76mm |
| 89600 – 76mm | | 89695 – 108mm |
| 89601 – 108mm | N12 Elbow | |
| 89697 – 133mm | 88456 – 67mm | N69P Straight Male Union connector |
| 89698 – 159mm | 89619 – 76mm | 89253 – 67mm x 2.1/2" |
| N11M Met x Imp Adaptor Coupling | N18 Slow Bend | N1FMGI Bi-Metal Flange |
| 89617 – 76mm x 3" | 89639 – 67mm | 88028 – 42mm (4 Holes) |
| 89618 – 108mm x 4" | 89640 – 76mm | 88029 – 54mm (4 Holes) |
| | 89741 – 108mm | 88114 – 67mm (4 Holes) |
| N3 Straight Male Connector | 89709 – 133mm | 89603 – 76mm (8 Holes) |
| 88200 – 67mm x 2.1/2" | 89710 – 159mm | 89604 – 108mm (8 Holes) |
| 89615 – 76mm x 3" | | 89602 – 133mm (8 Holes) |
| 89616 – 108mm x 4" | N21 Obtuse Elbow | 89719 – 159mm (8 Holes) |
| | 88653 – 67mm | |
| N6 Reducer | 89645 – 76mm | N1FMB Gunmetal Flange |
| 88310 – 67mm x 28mm | 89646 – 108mm | 89605 – 76mm (8 Holes) |
| 88311 – 67mm x 35mm | 89711 – 133mm | |
| 88312 – 67mm x 42mm | 89712 – 159mm | |
| 88313 – 67mm x 54mm | | |
| 89624 – 76mm x 35mm | N24 Equal Tee | |
| 89625 – 76mm x 42mm | 88719 – 67mm | |
| 89626 – 76mm x 54mm | 89648 – 76mm | |
| 89627 – 76mm x 67mm | 89649 – 108mm | |
| 89630 – 108mm x 42mm | 89713 – 133mm | |
| 89631 – 108mm x 54mm | 89714 – 159mm | |
| 89632 – 108mm x 67mm | | |
| 89633 – 108mm x 76mm | N25 Tee Reduced Branch | |
| 89699 – 133mm x 42mm | 88807 – 67mm x 67mm x 28mm | |
| 89700 – 133mm x 54mm | 89055 – 67mm x 67mm x 35mm | |
| 89701 – 133mm x 67mm | 89056 – 67mm x 67mm x 42mm | |
| 89702 – 133mm x 76mm | 89057 – 67mm x 67mm x 54mm | |
| 89703 – 133mm x 108mm | 89058 – 76mm x 76mm x 28mm | |
| 89704 – 159mm x 54mm | 89000 – 76mm x 76mm x 35mm | |
| 89705 – 159mm x 67mm | 89654 – 76mm x 76mm x 42mm | |
| 89706 – 159mm x 76mm | 89001 – 76mm x 76mm x 54mm | |
| | | |
| Copper body | | |
| 89707 – 159mm x 108mm | 89059 – 108mm x 108mm x 35mm | |
| 89708 – 159mm x 133mm | 89660 – 108mm x 108mm x 54mm | |
| | 89002 – 108mm x 108mm x 76mm | |
| | 89715 – 133mm x 133mm x 54mm | |
| | 89716 – 133mm x 133mm x 108mm | |
| | 89717 – 159mm x 159mm x 54mm | |
| | 89718 – 159mm x 159mm x 133mm | |

UK Approval Certificate (page 2 of 2)

Appendix to Certificate 2010723

| |
|---|
| SIZE: See model |
| SCOPE: Supplier recommended Maximum Working Pressure 18.6 Bar & Maximum Temperature 100°C Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C Above Ground use only |
| MATERIALS Non-Metallic Materials assessed (BS6920) to point of discharge |
| BACKFLOW PROTECTION NOTES N/A |
| MARKING Endex on body |
| ADDITIONAL NOTES N/A |

Extra Notes