



OFFICIAL LISTING

NSF certifies that the products appearing on this Listing conform to the requirements of Water Fittings, System Components and Materials - Verification of Regulatory Compliance with UK Regulation 4

This is the Official Listing recorded on November 5, 2021.

Aalberts Integrated Piping Systems Ltd.
St Catherines Avenue
Doncaster, Yorkshire DN4 8DF
United Kingdom

Facility: # 1 UK

Trade Name	Size	Installation Requirements
Resident Valves [1] [2] [3]		
Pegler RES1 Resident Valve 3/4x1 MF (5A3001)	[4]	
Pegler RES2 Resident Valve Plus 1 FF	[4]	
Pegler RES2 Resident Valve Plus 3/4 FF	[4]	
Pegler RES1 Resident Valve 1x1 MF (5A3002)	[4]	

- [1] Resident Valves in DZR brass. The valves feature a water meter manifold, pressure reducing valve, two non-return valves, a ball valve at the inlet and an optional drain off ball valve at the outlet.
- [2] Maximum working pressure 16.0 Bar. The outlet pressure range is 1.5 to 6.0 bar. Cold water use only.
- [3] Markings: Main body - Pegler brand and logo, flow arrow, size, pressure and CR on body. Ball valves - Pegler brand and logo, England, CR, PN on body. PVR cartridge - lift, direction arrows and adjust symbols on cap.
- [4] Combinations of 1" BSP female, 3/4" BSP female adaptor and 1" BSP male

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.