

## Model 7707N

File Number: EX4688

### COMPANY

**Aalberts integrated piping systems APAC Inc**

295 SEC 3 WANDAN RD  
WANDAN TOWNSHIP  
PINGTUNG HSIEN, 913 Taiwan

### MODEL INFO

7707N  
Coupling

COUPLINGS, FLANGE ADAPTERS			
Outlet Type	Pipe Type	Size, NPS (unless otherwise indicated)	Rated Pressure, psig (kPa)
Grooved, Cut, Grooved, Rolled	Sch. 30 (0.375 in. wall thickness)	14	300 (2068)
Grooved, Cut, Grooved, Rolled	Sch. 30 (0.375 in. wall thickness)	16	300 (2068)
Grooved, Cut, Grooved, Rolled	ASTM A53 standard wall	18	300 (2068)
Grooved, Cut, Grooved, Rolled	Sch. 20 (0.375 in. wall thickness)	20	300 (2068)



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."