

FDNP.MH29445 - Drinking Water System Components

Drinking Water System Components

[See General Information for Drinking Water System Components](#)**AALBERTS INTEGRATED PIPING SYSTEMS APAC INC**295 SEC 3 WANDAN RD
WANDAN TOWNSHIP
PINGTUNG HSIEN, 913 TAIWAN

MH29445

NSF/ANSI 61**Joining and Sealing Materials**

Trade Dsg	Water Contact Temp (°C)	Water Contact Mtl	Surface Area to Volume Ratio
Coupling			
7705 Standard Flexible Coupling (1 1/4"-12")(u)(x)	82	EPDM	-
7706 Reducing Coupling (1 1/2" x 1 1/4" - 8"x 6")(v)	82	EPDM	-
7707 Heavy Duty Flexible Coupling (1 1/4" - 24") (u)(x)	82	EPDM	-
7707N Heavy Duty Flexible Coupling(14"-24")(u)(x)	82	EPDM	-
7771 Standard Rigid Coupling (1 1/2"-24")(u)(x)	82	EPDM	-
A505 Coupling (3" - 12")(i)	82	EPDM	-
A507 Transition Coupling (3" - 12")(j)	82	EPDM	-
C305 Rigid Coupling (Copper Tubing) (2"-6")(x)	82	EPDM	-
C306 Reducing Coupling (2 1/2" x 2" - 6"x 4")(v)	82	EPDM	-
C307 Transition Coupling (2"-6")(t)	82	EPDM	-
K-9 Rigid Coupling (1 1/4" - 8")(u)(x)	82	EPDM	-
R20 Flexible Coupling (2" - 8")(u)(x)	82	EPDM	-
SS-1200 Stainless Steel High Pressure Flexible Coupling (3/4"-4") (z)	82	EPDM	-
SS-28 Stainless Steel Hinged Lever Coupling (1 1/2"-6")(u)(x)	82	EPDM	-
SS-5 Stainless Steel Rigid Coupling(1 1/4"-8")(u)(x)	82	EPDM	-
SS-7 Stainless Steel Rigid Coupling(1 1/4"-8")(u)(x)	82	EPDM	-

SS-7X Stainless Steel Heavy Duty Rigid Coupling(10"-24")(u)(x)	82	EPDM	-
SS-8 Stainless Steel Flexible Coupling (1 1/4"-8")(u)(x)	82	EPDM	-
SS-8X Stainless Steel Heavy Duty Flexible Coupling (1 1/4"-8")(u)(x)	82	EPDM	-
XH-1000 Extra Heavy Rigid Coupling (2"-12")(u)(x)	82	EPDM	-
Z05 Rigid Coupling (1 1/4"- 8")(u)(x)	82	EPDM	-
Z07N Heavy Duty Rigid Coupling (1 1/4"-24")(u)(x)	82	EPDM	-
Dielectric Fittings			
DE30-GG Dielectric Fittings (2" - 8") [Annex G]	82	Polyethylene	-
EPDM Gaskets			
Fast-Fit Grade E-pw EPDM Gasket (3/4" - 8") (A)	82	EPDM	-
Grade E-pw EPDM Flange Gasket (2" - 24") (A)	82	EPDM	-
Grade E-pw EPDM Flange Gasket (for copper tubings) (2" - 8") (A)	82	EPDM	-
Grade E-pw EPDM GapSeal Gasket (1-1/4" - 24") (A)	82	EPDM	-
Grade E-pw EPDM GapSeal Gasket (for copper tubings) (2" - 8") (A)	82	EPDM	-
Grade E-pw EPDM Reducing Gasket (2" x 1-1/2" - 8"x6") (A)	82	EPDM	-
Grade E-pw EPDM Standard Gasket (3/4" - 24") (A)	82	EPDM	-
Grade E-pw EPDM Transition Gasket 2" - 6"	82	EPDM	-
Flange Adapter			
7041 Flange Adapter(2"-24") (y)	82	EPDM	-
7043 Flange Adapter(2"-12") (y)	82	EPDM	-
A512 Flange Adapter (3" - 12")(h)	82	EPDM	-
C341 Flange (Copper Tubing) (2"-6")(y)	82	EPDM	-
SS-41 Stainless Steel Flange Adapter (2"-8")(y)	82	EPDM	-
Halogenated Butyl Gaskets			
Grade M Halogenated Butyl Flange Gasket (3"-24")	82	-	-
Grade M Halogenated Butyl GapSeal Gasket (3"-24")	82	-	-
Grade M Halogenated Butyl Transition Gasket (3"-12")	82	-	-
Stainless Steel Fittings			
SS-80 Universal Flange Adapter 2in to 12in [Annex G]	23	Stainless Steel	-

Mechanical Devices

Trade Dsg	Water Contact Temp (°C)	Water Contact Mtl	Surface Area to Volume Ratio
Butterfly Valve			
SJ-300N - Sizes 2" - 24" [Annex G]	82	-	-
SJ-400# - Sizes 2" - 8" [Annex G]	82	-	-
SJ-C300 - Sizes 2" - 6" [Annex G]	82	-	-

Pipes and Related Products

Trade Dsg	Water Contact Temp (°C)	Water Contact Mtl
Bronze Fittings		
C10 90 deg Elbow (2 in. - 8 in.)	82	Bronze
C11 45 deg Elbow (2 in. - 8 in.)	82	Bronze
C20 Tee (2 in. - 8 in.)	82	Bronze
C21 Reducing Tee - GR x GR x GR (2-1/2 in. x 2-1/2 in. x 2 in. - 6 in. x 6 in. x 5 in.)	82	Bronze
C26 Reducing Tee - GR x GR x CUP (2 in. x 2 in. x 3/4 in. - 4 in. x 4 in. x 2 in.)	82	Bronze
C50 Concentric Reducer - GR x GR (2-1/2 in. x 2 in. - 6 in. x 5 in.)	82	Bronze
C52 Concentric Reducer - GR x CUP (2 in. x 3/4 in. - 4 in. x 2 in.)	82	Bronze
C55 Transition Adapter (1-1/2" x 2" - 3" x 3")	82	Bronze
C60 Cap (2 in. - 8 in.)	82	Bronze
Stainless Steel Fittings		
SS-10 90° Elbow	82	Stainless Steel
SS-11 45° Elbow	82	Stainless Steel
SS-20 Tee	82	Stainless Steel
SS-21 Reducing Tee	82	Stainless Steel
SS-21 Reducing Tee	82	Stainless Steel
SS-21F Reducing Tee	82	Stainless Steel
SS-21F Reducing Tee	82	Stainless Steel
SS-50 Concentric Reducer	82	Stainless Steel
SS-50 Concentric Reducer	82	Stainless Steel
SS-50F Concentric Reducer	82	Stainless Steel

SS-50F Concentric Reducer	82	Stainless Steel
SS-60 Cap	82	Stainless Steel

[Annex G] - Product is certified to NSF/ANSI 372 and conforms to the lead content requirements for "lead free" plumbing as defined by California, Louisiana, Maryland and Vermont state law, and the U.S. Safe Drinking Water Act.

- May be any letter representing external product characteristics

A - Product For Use Only in Pipe Applications

h - Product manufactured using NSF 61/ 372 Certified Grade M Halogenated Butyl Flange Gasket

i - Product manufactured using NSF 61/ 372 Certified Grade M Halogenated Butyl GapSeal Gasket

j - Product manufactured using NSF 61/ 372 Certified Grade M Halogenated Butyl Transition Gasket

t - Product manufactured using NSF 61/ 372 Certified Grade E-pw EDPM Transition Gasket

u - Product manufactured using NSF 61/ 372 Certified Grade E-pw EDPM Standard Gasket

v - Product manufactured using NSF 61/ 372 Certified Grade E-pw EDPM Reducing Gasket

x - Product manufactured using NSF 61/ 372 Certified Grade E-pw EDPM GapSeal Gasket

y - Product manufactured using NSF 61/ 372 Certified Grade E-pw EDPM Flange Gasket

z - Product manufactured using NSF 61/ 372 Certified Fast-Fit Grade E-pw EDPM Gasket

Trademark and/or Tradename: "SHURJOINT" , **SHURJOINT**

Last Updated on 2020-12-17

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"