

SHURJOINT Model SS-8

Product Description

	SS-8 ^{a, b}																						
	Nominal Pipe Size																						
Pipe Description	1 (33.4)	1-1/4 (42.7)	1-1/2 (48.3)	2 (60.3)	2-1/2 (73.1)	(76.1)	3 (88.9)	(108.0)	4 (114.3)	(133.0)	(139.7)	5 (141.3)	(159.0)	(165.1)	6 (168.3)	8 (219.1)	10 (273.0)	12 (323.9)	14 (355.6)	16 (406.4)	18 (457.2)	20 (508.0)	24 (610.0)
Schedule 40, Cut Groove	300 (2070)	300 (2070)	300 (2070)	300 (2070)	300 (2070)		300 (2070)		300 (2070)			300 (2070)		300 (2070)		300 (2070)		N/A	N/A				
Schedule 40, Roll Groove	300 (2070)	300 (2070)	300 (2070)	300 (2070)	300 (2070)		300 (2070)		300 (2070)			300 (2070)		300 (2070)		300 (2070)	N/A				N/A	N/A	
Schedule 30, Cut Groove																	N/A	N/A					
Schedule 30, Rolled Groove	300 (2070)	300 (2070)	300 (2070)	300 (2070)	N/A		300 (2070)							300 (2070)									
ThinWall Pipes																					N/A	N/A	
Allied Tube & Conduit, "XL"									N/A														
Allied Tube & Conduit, "BLT"									N/A		N/A	N/A								N/A	N/A		
Allied Tube & Conduit, "Dyna-Thread"					N/A		N/A			N/A													
Bull Moose Tube, "EDDY-Thread 40"				N/A							N/A		N/A										
Blue Steel, "Rapid-Thread"																N/A							

[illegible]

Remarks:
a. FM Approved when supplied with an EPDM Gasket
b. Stainless Steel

Details

Category	Grooved Couplings, Standard-Flexible
Class of Work	1920 - Coupling & Fitting, All Type
Approval Standard	FM 1920 - Pipe Couplings and Fittings for Aboveground Fire Protection Systems
Certification Type	FM Approved
Listing Country	Taiwan

Company

Aalberts integrated piping systems APAC Inc.
No. 295, Sec. 3 Wantan Road, Wantan Pingtung, Taiwan
(R.O. C) 913
<http://shurjoint.com>