

VIZM.EX4688 - Fittings, Rubber Gasketed

Fittings, Rubber Gasketed

[See General Information for Fittings, Rubber Gasketed](#)**AALBERTS INTEGRATED PIPING SYSTEMS APAC INC**

EX4688

295 SEC 3 WANDAN RD
 WANDAN TOWNSHIP
 PINGTUNG HSIEN, 913 TAIWAN

Coupling

Model	Groove Type	Pipe	Size In.	Rated Pressure (psig)
7705	Rolled	5	1-1/4, 1-1/2, 2, 2-1/2, 3	175
7705	Rolled	MODULE-FLOW	1, 1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3, 4	300
7705	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	300
7705	Rolled	10 (0.188 in.)	10	175
7705	Rolled, Cut	30 (0.330 in.)	12	175
7705	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	300
7705	Rolled, Cut	40	10, 12	250
7705	Rolled, Cut	BS1387(M)	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6	300
7705	Rolled	DF, XL, XL-II	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
7705	Rolled	EF	1-1/2, 2, 2-1/2, 3	175
7705	Rolled	EL	1-1/4, 1-1/2, 2	300
7705	Rolled	SPS	1-1/4, 2, 2-1/2, 3	175
7706	Rolled	10	2x1-1/2; 2-1/2x2; 3x2, 2-1/2; 4x2, 2-1/2, 3; 6x3, 4; 8x6	300
7706	Rolled, Cut	40	2x1-1/2; 2-1/2x2; 3x2, 2-1/2; 4x2, 2-1/2, 3; 6x3, 4; 8x6	300
7706	Rolled, Cut	BS1387(M)	3.0 ODx2, 3; 4x2-1/2, 3; 6x4	300
7707	Rolled	10	3/4, 1, 1-1/4	500
7707	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8	450
7707	Rolled	10 (0.188 in.)	10, 12	300
7707	Rolled	40	10, 12	300
7707	Rolled, Cut	20 (0.375 in.)	18, 20, 24	250
7707	Rolled, Cut	30 (0.375 in.)	14, 16	300
7707	Rolled	40	3/4, 1, 1-1/4, 2, 2-1/2, 3, 4, 5, 6, 8	500

7707	Rolled	BS1387(M)	2-1/2, 5, 6	500
7707	Rolled	DF	1-1/2, 4	450
7771	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8	300
7771	Rolled	10	10, 12	175
7771	Rolled, Cut	20 (0.375 in.)	18, 20	300
7771	Rolled, Cut	20 (0.375 in.)	22, 24	250
7771	Rolled, Cut	30 (0.375 in.)	14, 16	300
7771	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6, 8	300
7771	Rolled, Cut	40	10, 12	175
7771	Rolled, Cut	BS1387(M)	2, 2-1/2, 3, 4, 5, 6	300
7771	Rolled, Cut	KS D 3507	216.3 mm	300
7771	Rolled, Cut	KS D 3507	267.4 mm, 318.5 mm	175
K-9	Rolled	5	1-1/4, 2, 2-1/2, 3	175
K-9	Rolled	MODULE-FLOW	1-1/4, 1-1/2, 2, 3 OD (76.1 mm), 3, 4	300
K-9	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	300
K-9	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	300
K-9	Rolled, Cut	BS1387(M)	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8, 3.0 OD, 6.5 OD	300
K-9	Rolled	DF	2, 2-1/2, 3, 4	175
K-9	Rolled	EL	1-1/4, 2	300
K-9	Rolled, Cut	ET40	2	300
K-9	Rolled	SPS	1-1/4, 2, 2-1/2, 3	175
K-9	Rolled	XL, XL-II	2, 2-1/2, 3	175
R20	Rolled	5	2	175
R20	Rolled	10	2, 3, 4	300
R20	Rolled, Cut	40	2, 3, 4	300
R20	Rolled, Cut	BS1387(M)	2, 2-1/2, 3, 4, 5, 6	300
R20	Rolled	DF	2, 3, 4	300
R20	Rolled, Cut	EL	2	300
SS-7	Rolled	10S, 40S	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	300
SS-7	Rolled	10S, 40S	76.1 mm, 139.7 mm, 165.1 mm	300
SS-8	Rolled	10S, 40S	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5	300
SS-8	Rolled	10S, 40S	6	250
SS-8	Rolled, Cut	40S	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5	300

SS-8	Rolled, Cut	40S	6	250
Z05	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 6, 8	350
Z05	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	350
Z05	Rolled	5	1-1/4, 1-1/2, 2	175
Z05	Rolled	BLT	1-1/4, 1-1/2, 2	300
Z05	Rolled	DF	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
Z05	Rolled	EF	1-1/4, 1-1/2, 2, 2-1/2, 3	175
Z05	Rolled	EL	1-1/4, 1-1/2, 2	300
Z05	Rolled	EZF	3, 4	300
Z05	Rolled	EZF	6	175
Z05	Rolled	MF	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
Z05	Rolled	MLT, WLS	1-1/4, 1-1/2, 2	300
Z05	Rolled	MT	1-1/4, 2	300
Z05	Rolled	XL	1-1/4, 1-1/2, 2	300
Z05	Rolled	BS1387(M)	1-1/4, 1-1/2, 2, 3, 4	350
Z05	Rolled	BS1387(M)	76.1 mm	300
Z07	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500
Z07	Rolled	10	5, 6, 8	400
Z07	Rolled	10	10	350
Z07	Rolled	20	12	350
Z07	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500
Z07	Rolled, Cut	40	5, 6, 8	400
Z07	Rolled, Cut	40	10, 12	350
Z07	Rolled, Cut	5	1-1/4, 1-1/2, 2	175
Z07	Rolled, Cut	DF	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
Z07	Rolled	EF	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	175
Z07	Rolled	EL	1-1/4, 1-1/2, 2	300
Z07	Rolled	EZF	3,4	300
Z07	Rolled	EZF	6	175
Z07	Rolled	MF	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
Z07	Rolled	MLT,WLS	1-1/4, 1-1/2, 2	300
Z07	Rolled, Cut	KS D 3507	216.3mm	400
Z07	Rolled, Cut	KS D 3507	267.4 mm, 318.5 mm	350

Z07N	Rolled, Cut	STD	14, 16	175
------	-------------	-----	--------	-----

Flange adapter

Model	Groove Type	Pipe	Size In.	Rated Pressure (psig)
7041	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8	175
7041	Rolled	10 (0.188 in.)	10	175
7041	Rolled, Cut	30 (0.330 in.)	12	175
7041	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6, 8	175
7041	Rolled, Cut	BS1387(M)	3.0 O.D., 4, 5	175
7043	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12	300
7043	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12	300
C341	Rolled	Type K, Type L	2, 2-1/2, 3, 4, 5, 6	200
SS-41	Rolled	10S	2, 2-1/2, 3, 4, 6	175

Side outlet

Model	Outlet Type	Pipe	Size In.	Rated Pressure (psig)
723	Threaded	10, 40, DF	1-1/4x1/2, 3/4, 1; 1-1/2x1/2, 3/4, 1; 2x1/2, 3/4, 1; 2-1/2x1/2, 3/4, 1	300
723	Threaded	EF	1-1/2x1; 2x1	300
723	Threaded	BS1387(M), XL, XL-II	1-1/4x1/2, 3/4, 1; 1-1/2x1/2, 3/4, 1; 2x1/2, 3/4, 1; 2-1/2x1/2, 3/4, 1	175
7721	Threaded	10, 40, BS1387(M)	2x1/2, 3/4, 1, 1-1/4, 1-1/2; 2-1/2x1/2, 3/4, 1, 1-1/4, 1-1/2; 3x1, 1-1/4, 1-1/2, 2; 4x1, 1-1/4, 1-1/2, 2, 2-1/2, 3; 6x1-1/4, 1-1/2, 2, 2-1/2, 3, 4; 8x2, 2-1/2, 3, 4	300
7722	Grooved	10, 40, BS1387(M)	3x1-1/2, 2; 4x1-1/2, 2, 2-1/2, 3; 6x1-1/2, 2, 2-1/2, 3, 4; 8x2, 2-1/2, 3, 4	300
C-7	Threaded	10, 40	1-1/2x1/2, 3/4, 1; 2x1/2, 3/4, 1; 2-1/2x1/2, 3/4, 1; 3x3/4, 1; 4x3/4, 1; 6x1, 1-1/2	300
C-7G	Grooved	10, 40	2x1; 2-1/2x1-1/4, 1-1/2; 3x1, 1-1/2; 4x1-1/2, 2; 6 x 1-1/2, 2	300
SS-723	Threaded	10S, 40S	1-1/4x1/2, 3/4, 1; 1-1/2x1/2, 3/4, 1; 2x1/2, 3/4, 1	300
M21	Thread	10, 40, EZF	4x3; 6x3, 4;	175
M21	Thread	MF	4x3; 6x3;	175
M21	Thread	FF, DF	4x3;	175
M21	Thread	BS1387(M)	6x3, 4;	175
M21	Thread	10, 40	2x1/2, 3/4, 1, 1-1/4, 1-1/2; 2-1/2x1/2, 3/4, 1, 1-1/4, 1-1/2; 3x1/2, 3/4, 1, 1-1/4, 1-1/2, 2; 4x1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2; 6x1-1/4, 1-1/2, 2, 2-1/2;	300

M21	Thread	40	5x 2, 2-1/2, 3;	300
M21	Thread	MF	2x1/2, 3/4, 1; 2-1/2x1/2, 3/4, 1, 1-1/4, 1-1/2; 3x1/2, 3/4, 1, 1-1/4, 1-1/2, 2; 4x1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2; 6x1-1/4, 1-1/2, 2, 2-1/2;	300
M21	Thread	EZT	2x1/2, 3/4, 1, 1-1/4, 1-1/2;	300
M21	Thread	FF	2x1/2, 3/4, 1; 2-1/2x1/2, 3/4, 1, 1-1/4, 1-1/2; 3x1/2, 3/4, 1, 1-1/4, 1-1/2, 2; 4x1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2;	300
M21	Thread	DF	2x1/2, 3/4, 1, 1-1/4, 1-1/2; 2-1/2x1/2, 3/4, 1, 1-1/4, 1-1/2; 3x1/2, 3/4, 1, 1-1/4, 1-1/2, 2; 4x1/2, 3/4, 1, 1-1/4, 1-1/2, 2;	300
M21	Thread	DF	4x2-1/2;	200
M21	Thread	EF	2x1/2, 3/4, 1, 1-1/4, 1-1/2; 2-1/2x1/2, 3/4, 1, 1-1/4, 1-1/2; 3x1/2, 3/4, 1, 1-1/4, 1-1/2, 2;	300
M21	Thread	EZF	3x1/2, 3/4, 1, 1-1/4, 1-1/2, 2; 4x1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2; 6x 1-1/4, 1-1/2, 2, 2-1/2;	300
M21	Thread	BS1387(M)	2-1/2x1/2, 3/4, 1, 1-1/4, 1-1/2; 5x2, 2-1/2, 3; 6x1-1/4, 1-1/2, 2, 2-1/2;	300
M22	Grooved	10, 40, EZF	4x3; 6x3, 4;	175
M22	Grooved	MF	4x3; 6x3;	175
M22	Grooved	FF	4x3;	175
M22	Grooved	BS1387(M)	6x3, 4;	175
M22	Grooved	10, 40	2x1, 1-1/4; 2-1/2x1, 1-1/4, 1-1/2; 3x1, 1-1/4, 1-1/2, 2; 4x1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1 mm; 6x1-1/4, 1-1/2, 2, 2-1/2;	300
M22	Grooved	40	5x2, 2-1/2, 76.1 mm, 3;	300
M22	Grooved	MF	2x1; 2-1/2x1, 1-1/4, 1-1/2; 3x1, 1-1/4, 1-1/2, 2; 4x1, 1-1/4, 1-1/2, 2, 2-1/2; 6x1-1/4, 1-1/2, 2, 2-1/2	300
M22	Grooved	FF	2x1; 2-1/2x1, 1-1/4, 1-1/2; 3x1, 1-1/4, 1-1/2, 2; 4x1, 1-1/4, 1-1/2, 2, 2-1/2	300
M22	Grooved	DF	2x1, 1-1/4, 1-1/2; 2-1/2x1, 1-1/4, 1-1/2; 3x1, 1-1/4, 1-1/2, 2; 4x1	300
M22	Grooved	EF	2x1, 1-1/4, 1-1/2; 2-1/2x1, 1-1/4, 1-1/2; 3x1, 1-1/4, 1-1/2, 2	300
M22	Grooved	EZF	3x1, 1-1/4, 1-1/2, 2; 4x1, 1-1/4, 1-1/2, 2, 2-1/2; 6x 1-1/4, 1-1/2, 2, 2-1/2	300
M22	Grooved	BS1387(M)	2-1/2x1, 1-1/4, 1-1/2; 4x2-1/2, 76.1 mm; 5x2, 2-1/2, 76.1 mm, 3; 165.1 mmx1-1/4, 1-1/2, 2, 76.1 mm	300

Models 7705, 7707, 7771, K-9, Z05 and Z07 incorporating Lube-E (Pre-lubricated) gasket are suitable for use in dry pipe systems for temperatures to -40°C.

Models 7705, 7707, 7771, K-9, Z05 and Z07 in following descriptions incorporating Lube-E (Powder Coated) gasket are suitable for use in dry pipe systems for temperatures to -40°C.

Model 7705: from 1 to 12 in. sizes.

Model 7707: from 3/4 to 8 in. sizes.

Model 7771: from 2 to 12 in. sizes.

Model K-9: from 1-1/4 to 8 in. sizes.

Model Z05: from 1-1/4 to 8 in. sizes.

Model Z07: from 1-1/4 to 12 in. sizes.

Models C341 and SS-7 incorporating Lube-E gasket are also suitable for use in dry pipe systems for temperatures to -40°C.

Models 723 and SS-723 in the 1/2 and 3/4 in. nominal outlet sizes are intended for direct connection to sprinklers.

Model 7721 and C-7 in the 1/2, 3/4, and 1 in. nominal outlet sizes are intended for direct connection to sprinklers.

Models 723 C-7G, C-7, and SS-723 the 1 in. and larger nominal outlet sizes are intended for connection to system piping.

Model M21 in the 1/2 in and 3/4 in. nominal outlet sizes are intended for direct connection to sprinklers.

Models M21 and M22 in the 1 in. and larger nominal outlet sizes are intended for connection to system piping.

5 refers to Listed Schedule 5 steel pipe manufactured by Allied Tube & Conduit Corp.

10 refers to Schedule 10 steel pipe.

20 refers to Schedule 20 steel pipe.

30 refers to Schedule 30 steel pipe.

40 refers to Schedule 40 steel pipe.

10S refers to Schedule 10 stainless steel pipe manufactured in accordance with ASTM A312.

40S refers to Schedule 40 stainless steel pipe manufactured in accordance with ASTM A312.

Type K refers to Type K copper pipe manufactured to ASTM B88.

Type L refers to Type L copper pipe manufactured to ASTM B88.

BS1387(M) refers to British Standard Medium steel pipe.

BLT refers to Listed BLT steel pipe manufactured by Allied Tube & Conduit Corp

DF refers to Listed DYNA-FLOW steel pipe manufactured by Allied Tube & Conduit Corp.

EF refers to Listed EDDY FLOW steel pipe manufactured by Bull Moose Tube Co.

EL refers to Listed EDDYLITE steel pipe manufactured by Bull Moose Tube Co.

ET40 refers to Listed Eddythread 40 steel pipe manufactured by Bull Moose Tube Co.

EZF refers to Listed E-Z- Flow steel pipe manufactured by Northwest Pipe Co.

MF or MFGF refers to Listed Mega-Flow and Mega-Flow-GF steel pipe manufactured by Wheatland Tube Co Wh Div.

MLT refers to Listed MLT and GL steel pipe manufactured by Wheatland Tube Co Wh Div.

MT refers to Listed Mega-Thread and Mega-Thread-GT steel pipe manufactured by Wheatland Tube Co Wh Div.

SPS refers to Listed SPS Flow steel pipe manufactured by Shin Yang Steel Co Ltd.

STD refers to STD weight class steel pipe manufactured in accordance with ASTM A53.

WLS refers to Listed WLST steel pipe manufactured by Wheatland Tube Co Wh Div.

XL, XL-II refers to Listed XL, XL-II steel pipe manufactured by Allied Tube & Conduit Corp.

EZT refers to Listed EZ-Thread steel pipe manufactured by Youngstown Tube Co.

FF refers to Listed Fire-Flo steel pipe manufactured by Youngstown Tube Co.

KS D 3507 refers to Korean Industrial Standard KS D 3507-1985, Class SPP.

MODULE-FLOW refers to Listed MODULE-FLOW steel pipe manufactured by Josh Global Corp.

Trademark and/or Tradename:  **SHURJOINT** , "SJ", "SHURJOINT"

Last Updated on 2021-02-11

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"